



BOBST SP 142 E

Reference	23036346
Type	Die Cutting/fustellatrici
Manufacturer	Bobst
Model	SP 142 E
Year	1986
Serial Number	057402711

[REQUIRE MORE INFO-QUOTATION](#)

[VIEW DETAILS-GALLERY-VIDEO](#)

Accessories

- Console
 - Centerline
- Feeder
 - Motorized suction head unit
 - Pile feeder with automatic lateral moving
 - Universal Feeder
 - **Non-stop on feeder with swords**
- Introduction table
 - Sheet-hold down device (Introduction sheets guide in gripper)
 - Pull-lay operator side (OS) adjustable according to Centerline, with sheet control
 - **Receiving pull lay of the push lay operator side**
 - **PULL LAY OPERATOR OPPOSITE SIDE (OOS)**
 - **PUSHING LAY FOR CORRUGATE OPPOSITE OPERATOR SIDE (OOS)**
 - Electronic double sheet device
 - **D-7 REINFORCED SHEET TRANSPORT EQUIPMENT for rigid and corrugate cardboard included: Introducers and upper belts - Upper transport elements (wide belts)**
 - Adjustable sheet synchronizer while running, allows to adapt the feeder cycle to that of the platen
 - Feed table with 4 front lays, adjustable in pairs with front register control
 - Side-guided carrying straps
- Platin
 - **E-5 COMPENSATING PLATE. THICKNESS 4 MM. IN GROUND STEEL**
 - **E-55 ADJUSTABLE SUPPORTING PLATE CENTERINGS**
- Stripping Station
 - **1 "GRID" UPPER PULL-OUT FRAME WITH ALL ITS STANDARD TOOLS**
 - **CENTRAL PULL-OUT FRAME QUICK LOCK ON STRIPPING UNIT WITH ALL ITS TOOLS**
 - F-8 1 LOWER STRIPPING PULL-OUT FRAME WITH ALL ITS TOOLS
 - F-22 Fastening equipment for stripping die (including crossbars and clamps)
 - **F-35 FASTENING EQUIPMENT FOR UPPER PULL-OUT FRAME QUICK LOCK DEVICE**

FOR STRIPPING (TO FIX STRIPPING TOOL TO THE UPPER PULL-OUT FRAME QUICK LOCK)

- F-2 : N. 1 Upper pull-out frame
- F-81 LOWER STRIPPING EQUIPMENT for waste stripping INCLUDING crossbars, pins and supports (installed on central pull-out frame F-8)
- **Micrometric system with compensating plate and 1 mm small metals sheet**
- Delivery
 - Non-stop delivery with belt convey
 - **Safety sensors in delivery**
 - **Guillotine device for front trim**
- Various
 - **Elevated 350 mm**