

## **BOBST SP 104 E**

**Reference** 24036470

**Type** Die

Cutting/fustellatrici

**Manufacturer** Bobst

Model SP 104 E

**Year** 2002

**Serial Number** 057808001

N.of Impressions 91

**REQUIRE MORE INFO-QUOTATION** 

**VIEW DETAILS-GALLERY-VIDEO** 

## **Accessories**

- Machine
  - Platform safety barrier
  - Centerline system for quick job changeover
  - Electronic double sheet control
  - · Adjustable centering at the stripping and at the delivery
  - Air conditioning for the electrical cabinet
  - Gripper bars
  - Main motor with frequency variator
  - B-1 ELEVATED MACHINE Machine elevated 400 mm, included elevation of the steps
  - B-42 ADDITIONAL INTERFACE "CUBE". It includes an additional screen and keyboard located on the feeder, operator side, which facilitate the management of the machine.
  - F-9 PRE-SETTING TABLE: Adjustable. Allows the preparation of a second job during production, reducing machine makeready time and increasing the time available to run production. Requires: a series of supplementary stripping tools
- Feeder
  - Pile-tray with handle allowing manual lateral correction of the pile during production
  - Pile height control at the front edge thanks to a photoelectric cell
  - Pile rear guide (OS and OOS sides)
  - Adjustable lateral blowers with Centerline references
  - Suction unit with multiple adjusting
  - Safety system for lowering the pile try
  - C-4 NON-STOP FEEDER MANUAL DEVICE
  - C-8 VERTICAL POSITIONING OF THE SUCTION UNIT
  - C-17 AUTOMATIC SIDE CORRECTION OF THE PILE
  - Push lay opposite operator side
- Introduction table

- Covered with an anti-static stainless steel plate
- synchronization of the sheet adjustable at the stop, allows to adapt the speed of the feeder with which of the platin
- 4 front lays, adjustable in pairs with front register control
- Pull-lay operator side (OS) adjustable according to Centerline, with sheet control
- · Double sheet detector
- Sheet-hold down device (guiding the sheets to front lays)
- Upper transport equipment for paper, paperboard and corrugated board
- Upper sheet transport equipment for paper, cardbord and corrugate cardboard to 4 mm thickness
- 4 Transport belts lateral guide
- C-5 CONTROLLABLE SHEET ARRIVAL FOR PERFECT SYNCHRONIZATION OF SHEET ARRIVAL AND REDUCTION OF MACHINE STOPPAGES
- D-1 PULL GUIDE (OOS) with device for sheet presence control. Pull adjustable with Centerline references
- D-3 PUSH GUIDE (OOS opposite operator side) WITH ELECTRONIC CONTROL useful for thick carton and corrugate
- D-73 FEED BELT SLOW-DOWN DEVICE

## Platin

- Grippers re-opening device
- Die-cutting device without band of gripper grip
- Equipment centering and locking
- Locking of the chase against the upper beam
- Measurement of the die-cutting force with strain gauge
- Resocell: synthetic material supporting plate. Thickness 22.5 mm
- 1 Upper chase with quick locking: fixed bottom (E-3) Plate, thickness 2 mm and makeready protection plate of syntetic material, 1 mm thickness
- 1 Cutting plate (E-4)
- E-5 COMPENSATION PLATE 4 mm thickness. it's useful for thin plate for repetetive work
- E 55 ADJUSTABLE SUPPORTING PLATE CENTERINGS: micromeric screws allow fine adjustment of counters mounted on the cutting plate with respect to the die (+/- 0,9 mm lengthwise and crosswise.
- E-56 LOWERING DEVICE FOR THE CHAINS-GUIDE

## Stripping Station

- 3 drawer frame system
- 1 Upper Stripping Frame (F-2)
- 1 Upper stripping equipment (F-21) required to create a waste stripping tool, including crossbars, clamps, stripper holders and stripping pins of 3, 5 and 10 mm of diameter
- 1 Fastening equipment for stripping die (F-22)
- 1 Central drawer frame (F-71)
- 1 Fastening equipment stripping table (F-75)
- 1 lower pull-out frame (F-8)
- 1 Lower stripping equipment (F-81) Equipment for waste stripping including crossbars, pins and supports
- B-23 SHEET BRAKING DEVICE USING BERNOULLI SYSTEM AT STRIPPING SECTION
- F-2 1 UPPER STRIPPING FRAME 1 unit comes with the basic machine
- F-21 1 UPPER STRIPPING EQUIPMENT REQUIRED TO CREATE A WASTE STRIPPING TOOL, INCLUDING CROSSBARS, CLAMPS, STRIPPER HOLDERS AND STRIPPING PINS OF 3, 5 AND 10 MM OF DIAMETER
- F-22 1 FASTENING EQUIPMENT FOR STRIPPING STATION DIE
- F-31 1 UPPER PULL-OUT FRAME QUICK LOCK WITH ALL ITS TOOLS
- F-35 1 FASTENING EQUIPMENT FOR UPPER PULL-OUT FRAME QUICK LOCK DEVICE FOR STRIPPING (TO FIX STRIPPING TOOL TO THE UPPER PULL-OUT FRAME QUICK LOCK)
- F-72 1 CENTRAL PULL-OUT FRAME QUICK LOCK ON STRIPPING UNIT
- F-76 1 FASTENING EQUIPMENT FOR STRIPPING TABLE ON CENTRAL PULL-OUT FRAME QUICK LOCK It allows to equip a stripping table to install it on central pullout frame quick-lock

- F-81 1 LOWER STRIPPING EQUIPMENT. Equipment for waste stripping including crossbars, pins and supports
- F-8 1 LOWER STRIPPING FRAME
- F-91 1 DEVICE FOR ADJUSTING THE LOWER NEEDLES FROM A QUICK-LOCK STRIPPING TOOL. This device mounts to the F-2 upper stripping frame
- Delivery
  - Pile tray in delivery
  - Adjustable rear and side joggers with Centerline marks
  - Braking brush
  - Pneumatically controlled adjustable front joggers
  - Pushes the sheets down, ensuring good stacking
  - G-5 AUTOMATIC NON-STOP ON DELIVERY
- · Conformity to standards and security
  - The Autoplaten Presses SP 104-E is in conformity with the European Directives for the Safety and Health requirements related to its design and construction, sa well American standards UL 508 and NFPA related to industrial equipment
  - Emergency Stops
  - Operator safety devices
  - Gripper Bar Chain Slip Clutch
  - Handling of the diecutting equipment
  - Gripper bar chain locking device