

KOMORI GL 540 + C

Reference	26037563
Type	Sheetfed Offset
Manufacturer	Komori
Model	GL 540 + C
Year	2020
Serial Number	2456
N.of Impressions	131

REQUIRE MORE INFO-QUOTATION

VIEW DETAILS-GALLERY-VIDEO

Accessories

- Console
  - PQC-S: console for ink, axial, circumferential diagonal remote control
  - AMR (Automatic Make Ready): automatic preset for pressure, size format, autoplate, ink, etc,.
  - **PCC (Software) : CIP3/PPF converter for PQC format to transfer ink profile directly from pre-press to press**
  - **KHS-AI : Komori High Performance System - Advance Interface for Self-learning Function**
  - **KID : Wide Screen Komori for operative informations connected to KHS-AI and PDC-SX**
  - **KMS IV : Komori Monitoring System**
  - **PDC-SX (integrated type): Auto Tracking Spectrophotometer included register adjusting control**
  - **PQA-S V5 : inline colour measurement and control with sheet inspection**
  - **SIP : simultaneous profile pre-inking of all printing units**
  - **Smart Feedback : automatic density correction during production to reduce waste**
  - **AirPreset (KHS4) : storable air settings**
- Feeder
  - Suction belt on feeder
  - **Ultrasonic double-sheet control**
  - **Antistatic on feeder**
- Printing Units
  - Komorimatic dampening
  - Inking unit with remote distributor-roller adjustment
  - All wash-up device automatic
  - **Technotrans Beta.c 170L alcosmart (AZR) ink temp control combined with damping refrigeration, pH/conductivity display**
  - **FAPC fully automatic plate change**
  - **Skeleton Transfer cylinders with Venturi system**

    - **Ink and dampener declutch on units 1 & 5**
    - **Industrial diamond-coated grippers**
    - **Additional bridge roller between inking and dampening and additional rider roller on dampening form roller**
- Varnishing units
    - **Dedicated coating unit with TRESU chambered doctor blade and 1 anilox roller**
    - **TRESU Coating Circulator**
    - **Automatic blanket and impression cylinder wash on coating unit**
- Delivery
    - **Baldwin IVT IR dryer on delivery**
    - **Grafix Digitronic powder spray**
    - **Non-stop delivery**
    - **Extended delivery C version (double, approx. 2,000 mm) for coating unit**
    - **Grafix powder extraction**
    - **Tape inserter in delivery**
- Various
    - 16.500 speed/h
    - **Printable tickness capacity from 0.06 to 1 mm.**